

Reference Numbers				Dimensions				Minimum Capacity			Maximum Capacity		
Floyd	Meister	Neukomm	Dunner	Body Ø mm	Length mm	Thread	Cone	Ø mm	Hex mm	Sq mm	Ø mm	Hex mm	Sq mm
J2	1601	50.001	J2	7	30	6x0.5	16°	0.31	1.0	1.0	3.5	3.0	2.5
A1002	451	2.001	1002	9	30	--	19°	0.31	1.0	1.0	4.0	3.5	2.5
B201	351	150	B201	9	50	8x0.6	30°	0.31	1.0	1.0	5.0	4.5	2.5
J3	1351	51.001/200	J3	9	44	8x0.75	16°	0.31	1.0	1.0	5.0	4.5	3.0
A1004	453	6.001	1004	11	30	--	19°	0.31	1.0	1.0	6.5	5.5	4.5
1352	1352	--	--	11	53	10x0.8	16°	0.5	1.0	1.0	7.5	6.0	4.0
J4	--	3.001/203	J4	11	53	10x0.75	16°	0.5	1.0	1.0	7.5	6.0	5.0
B211	103	--	B211	12	50	12x1.0	30°	0.5	1.0	1.5	8.0	6.5	5.5
J5	1603	53.001	J5	12	50	10x0.75	16°	0.5	1.0	1.5	7.5	6.0	5.0
B300	3400T	113.001/10	B300	13	41.5	12.5x0.75	15°	0.7	1.0	1.5	8.0	7.0	5.0
B304	3300T	207 / 50	B304	14	64	13x0.75	16°	0.7	1.0	1.5	8.0	7.0	5.5
A1024	203	104.001	1024	16	40	--	30°	0.7	1.0	1.5	8.0	7.0	5.5
A1008	457	9.001	1008	16	30	--	30°	0.7	1.5	1.5	10.0	8.0	7.0
B203	603	--	B203	16	61	15x1.0	19°	0.7	1.5	1.5	11.0	9.5	8.0
1353	1353	8.001/206	J6R	16	59	14x1.0	16°	0.7	1.5	1.5	10.5	9.0	7.5
J6	1604	54.001/103	J6	16	58	14x1.0	16°	0.7	1.5	1.5	10.5	9.0	7.5
B212A	853	166.001/208	B212A	18	59	16x1.0	30°	1.0	1.5	2.0	12.0	11.0	9.0
Top 100	Top 100	--	--	18	100	18x1.0	20°	1.0	1.5	3.0	13.0	11.0	9.0
A1025	204	105.001	1025	20	40	--	30°	1.0	1.5	2.0	11.0	9.0	7.5
B208	104	--	B208	20	55	20x1.0	30°	1.0	1.5	2.0	13.0	11.0	9.0
N800	221T	450.001/800	B301	21	57.5	18x1.0	12°	1.5	2.0	2.0	11.0	9.5	8.0
J7A	1354	13.001	J7A	22	68	19x1.0	16°	1.5	2.0	2.0	16.0	14.0	11.0
39.001	39001T	39.001	J7AR	22	68	22x1.0	16°	1.5	2.0	2.0	18.0	15.0	13.0
A1010	459	15.001	1010	24	42	--	19°	1.5	2.0	2.0	15.0	13.0	10.0
B238	605	61.002/106	B238	24	61	24x1.0	30°	1.5	2.0	2.0	16.0	14.0	11.0

Reference Numbers				Dimensions				Minimum Capacity			Maximum Capacity		
Floyd	Meister	Neukomm	Dunner	Body Ø mm	Length mm	Thread (M)	Cone	Ø mm	Hex mm	Sq mm	Ø mm	Hex mm	Sq mm
B302	3402T	13	B302	27	57.5	24x1.0	12°	2.0	2.5	3.0	16.0	14.0	11.0
A1011	460	16.001	1011	28	45	--	29°	2.0	2.5	3.0	20.0	17.0	14.0
B260	1357	18.001	B260	28	81	25x1.0	30°	2.0	2.5	3.0	20.0	18.0	15.0
B261	223T	22.001	B261	28	82	25x1.0	16°	2.0	2.5	3.0	20.0	18.0	15.0
B261R*	--	--	--	28	82	27x1.0	16°	20.0	17.0	15.5	23.0	19.5	16.0
B261R*	--	--	--	28	82	28x1.0	16°	20.0	17.0	15.5	24.0	22.5	16.5
A1026	205	107.001	1026	30	60	--	29°	2.5	2.5	3.0	17.0	14.0	12.0
A1012	461	17.001	1012	32	45	--	19°	2.5	2.5	3.0	22.0	19.0	15.0
B214	355	110	B214	32	71	32x1.0	30°	2.5	2.5	3.0	22.0	19.0	15.0
A1027	206	108.001	1027	34	60	--	29°	2.5	3.0	3.0	22.0	19.0	15.0
N227	227T	451.004/227	B227	34	87.5	34x1.0	10°	2.5	3.0	4.0	25.0	22.0	18.0
Top 200	Top 200	Top 200	--	34	150	32x1.5	20°	3.0	3.0	4.0	26.0	22.0	18.0
A1013	462	20.001	1013	38	45	--	19°	3.0	3.0	4.0	28.0	24.0	19.0
A1030	463	21.001	1030	38	60	--	19°	3.0	3.0	4.0	28.0	24.0	19.0
B207	105	61.001	B207	40	71	40x1.0	30°	3.0	3.0	4.0	30.0	26.0	20.0
B207A	854	172.001	B207A	40	72	36x1.0	30°	3.0	4.0	4.0	26.0	22.0	20.0
A1028	207	110.001	1028	42	72	--	29°	3.0	4.0	4.0	26.0	22.0	20.0
A1032	465	29.001	1032	42	60	--	19°	3.0	4.0	4.0	28.0	24.0	20.0
N229	229T	28.001/229	J9	42	82	40x1.0	16°	4.0	4.0	4.0	32.0	26.0	20.0
N229R*	--	--	--	42	82	42x1.0	16°	32.0	27.0	21.0	36.0	30.0	24.0

* These Guide Bushes are reinforced oversized bushes. Special or modified nuts will be required. These are supplied with No Guarantee.